# TOYOPEARL® lon Exchanger

TOYOPEARL® Sulfate-650F

FOR IN VITRO USE ONLY / FOR PACKED-BED USE ONLY

# INSTRUCTION MANUAL



# **Safety Precautions**

To help protect you and/or your property from potential damage and ensure personal safety, please read this manual thoroughly before using the product.

## [Notation Conventions]

	<u>-</u>		
Notation		Explanation	
⚠ WARNING Indicates a hazard with a medium le result in death or serious injury.		Indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.	
	<b>⚠</b> CAUTION	Indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.	

#### **↑** WARNING

#### ■ Keep away from fire

Not taking proper precautions when using flammable solvents could result in fire, explosion, or poisoning.

#### **CAUTION**

#### ■ Use only in well-ventilated areas

In case of insufficient ventilation, flammable and toxic solvents can cause fire, explosion, or poisoning.

#### ■ Do not spill solvents

Spillage and leakage can cause fire, electric shock, poisoning, injury, or corrosion. Wear appropriate protective gear when cleaning up a spill.

#### Wear protective eve gear and gloves

Organic solvents and acids should not come into direct contact with the skin.

#### ■ Handle the package with care

Inappropriate handling may cause rupturing and/or splattering of the product.

## Only use this product for its intended use

This product is intended for the separation and purification of small molecules and proteins. Do not use it for any other purpose.

#### ■ Make sure compounds are safe

Check that the target compounds and solutions after separation and purification are safe.

#### Proper disposal

Dispose in accordance with local laws and regulations.

#### **NOTE**

Keep this manual with the product for future reference.

# Precautions: Shipping Solvents

First Aid	Inhalation	Move the person to an area with fresh air and rinse the mouth with plenty of water.
		Call immediately for medical attention.
	Skin exposure	Wash the exposed area with plenty of soap and water.
	Eye exposure	<ul> <li>Open eyes as wide as possible and rinse with clean water for at least 15 minutes.</li> <li>Call immediately for medical attention.</li> </ul>
	Ingestion	Rinse the mouth with plenty of water.     Call immediately for medical attention.
Handling and	Ventilation	<ul> <li>Provide adequate air ventilation to keep organic vapor concentrations below approved level.</li> </ul>
Storage	Container handling	Container may break if not handled with care.
	Wear appropriate protective equipment	Use solvent-resistant gloves and protective eye gear when using this product. Use of a gas mask, additional protective clothing or rubber boots could be appropriate when handling this product.
	Hazardous substance storage	If any flammable solvents are used for shipping or storage of this product, keep away from fire or open heat sources.
	Storage temperature	• Avoid storing this product at very low temperatures ( $<$ 0 °C) to prevent product from freezing.
Waste Disposal	Disposal methods	Dispose in accordance with local laws and regulations.
	General considerations	<ul> <li>Please pay attention to all safety precautions with respect to the handling and storage of this product.</li> </ul>
Note Ship	pping solvent; 20	% aqueous ethanol containing 0.2 mol/L sodium acetate

# Precautions: TOYOPEARL Brand Chromatographic Media

First Aid	Inhalation	Move the person to an area with fresh air and rinse the mouth with plenty of water.     Call immediately for medical attention.		
	Skin exposure	Wash the exposed area with plenty of soap and water.		
	Eye exposure	Open eyes as wide as possible and rinse with clean water for at least 15 minutes.     Call immediately for medical attention.		
	Ingestion	Rinse the mouth with plenty of water. Call immediately for medical attention.		
Handling and	Ventilation	Provide adequate air ventilation to keep organic vapor concentrations below approved level.		
Storage	Container handling	Container may break if not handled with care.		
	Wear appropriate protective equipment	Use solvent-resistant gloves and protective eye gear when using this product. Use of a gas mask, additional protective clothing or rubber boots could be appropriate when handling this product.		
	Hazardous substance storage	If any flammable solvents are used for shipping or storage of this product, keep away from fire and open heat sources.		
	Fire precautions	Do not expose this chromatographic resin to fire or open heat sources.		
Waste Disposal	Disposal methods	Dispose in accordance with local laws and regulations. See below for additional precautions.		
	General considerations	Please pay attention to all safety precautions with respect to the handling and storage of this product.		
	Disposal precaution	This product can be safely incinerated. Appropriate sulfur oxides exhaust emission precaution should be taken specifically for TOYOPEARL Sulfate-650F.		
Note TOYOPEARL products contain combustible chromatographic packings based on a methacrylate polymer.				

# Table of Contents

1.	Introduction	1
2.	Procedure for Chromatography ·····	1
3.	Storage ····	4
4	Remarks ·····	4

### 1. Introduction

TOYOPEARL Sulfate-650F is a strong cation exchanger for packed-column use, which consists of a porous and spherical polymer (particle size:  $30-60~\mu m$ ). TOYOPEARL Sulfate-650F has the following features.

- The quantity of gel listed on the container represents the volume of gravity settled resin and not the total liquid volume.
- The change of gel volume when packed into a chromatographic column is negligible in buffers at various pH or salt concentrations.
- · Applicable to fast flow-rate on column chromatography.
- · Resistant for microbial growth.
- · Applicable to most HPLC systems.

Note Under the acidic conditions (pH < 3), deterioration of the gel performance would occur.

# 2. Procedure for Chromatography

#### 2-1 Removal of Fines

- (1) As an example, pour the gel of 500 mL in the beaker of 3000 mL. (The capacity has six times of the gel.)
- (2) Add 2000 mL of distilled water (four times of the gel volume) to the beaker, stir and let the gel settle.
  - Note The necessary settling time for TOYOPEARL Sulfate-650F is approximately 45-60 minutes.
- (3) Decant and discard the supernatant (containing fines).
- (4) Repeat steps (2) and (3) of this process at least three times.




Figure 1 - Removal of Fines

#### 2-2 Cleaning

TOYOPEARL Sulfate-650F is shipped or stored in 20 % aqueous ethanol containing 0.2 mol/L sodium acetate.

The washing of the gel is necessary prior to use.

Pour the gel slurry on a glass filter and wash with distilled water of three times of the gel volume.

#### 2-3 Preparation of Gel Slurry and Packing

After removing fines from the gel by decantation (Section 2-1), wash the gel with packing buffer. The packing buffer should contain 0.5-1 mol/L NaCl. Transfer the gel into a beaker and add the packing buffer to make an approximately 30-50 % (V/V) (recommended) slurry. Packing the column under pressure (ca. 0.05-0.3 MPa) is recommended.

In this case a pump and a reservoir are necessary to pack the column.

Usually the packing flow rate is at least two times faster than that of the operating flow rate. Initial packing using a gravity-settled bed can be applied, however, applying pressure from flow rate or dynamic axial compression results in the best packed columns. For this resin, best results are obtained when the packing pressure

is as high as possible up to a limit of 0.1-0.3 MPa.

#### 2-4 Equilibration and Performance Testing

After packing, the column should be equilibrated with 3 to 5 column volume of buffer. The column should then be tested for packing integrity using a standard performance test.

#### 2-5 Sample Loading and Elution

The sample being purified is typically adsorbed onto the column using a low conductivity buffer. The sample is usually desorbed from the column using with an increasing salt gradient.

#### 2-6 Regeneration

The chromatographic resin can be regenerated after use by one of the following procedures.

#### 2-6-1 Batch method

Pour the gel into a beaker and suspend using an appropriate cleaning solvent. Stir and let the gel settle for approximately 45-60 minutes. Discard the supernatant by decantation.

Repeat this process 2 or 3 times.

- \* General cleaning method
  - First wash the gel with 1-2 mol/L NaCl solution using the procedure mentioned above. Then equilibrate the gel with the loading buffer.
- \* Severe cleaning method

Wash the gel with 0.1-0.5 mol/L NaOH followed by washing with 1-2 mol/L NaCl solution. Then equilibrate the gel with the loading buffer.

Note Acidic solutions (pH < 3) are not recommended as the cleaning solvent.

Deterioration of the gel performance would occur under the acidic conditions.

#### 2-6-2 Column Cleaning Method

The chromatographic resin in a packed column can be regenerated easily by flowing the cleaning solvents through the column. The solvents for the column cleaning are the same as those used in the Batch Method.

[Advantages of Column Cleaning Method]

\* Simple Handling Removing the gel from the column and repacking of the

chromatographic resin into the column are not

necessary.

\* Good Reproducibility Cleaning times are very consistent and reproducible.

\* Quick Cleaning By using a pump the cleaning times become shorter

than that used by the Batch Method.

\* Effective Cleaning The gel can be regenerated very well with small

amount of solvents compared with the Batch

Method.

# 3. Storage

The gel should be stored in 20 % aqueous ethanol containing 0.2 mol/L sodium acetate at ambient temperatures (4 - 35  $^{\circ}$ C)

## 4. Remarks

#### 4-1 Removal of Fines

As described in Section 2, remove fines before use. When the fines are not removed completely, there is a possibility that micro-particles may leach from column during chromatography. Leaching of the micro-particles, however, should stop after a short period of time.

#### 4-2 Clogging of Filter

Increasing of pressure-drop or decreasing flow-rate is typically caused by filter (frit) clogging. When this happens, remove the chromatographic resin from the column and clean the fitting and screens. Once the hardware is completely clean, repack the chromatographic resin into the column as described above.

#### 4-3 Adsorption of Protein

When the protein or other small molecule is not adsorbed onto the column with the initial buffer, the sample should be dialyzed or desalted to reduce the conductivity (recommended salt concentrarton: 0-0.3 mol/L). Alternatively, change the pH of the binding buffer.

## 4-4 Packing Method

Tosoh Corporation recommends packing the resin into the column using a pressure-packing method. Packing the column using a suction method or by just using gravity settling is not recommended, particularly for columns more than 10 cm in length.



# TOSOH CORPORATION BIOSCIENCE DIVISION

Shiba-Koen First Bldg.
3-8-2 Shiba, Minato-ku, Tokyo 105-8623, Japan
Phone: +81 3 5427 5180 Fax: +81 3 5427 5220
Web site: http://www.separations.asia.tosohbioscience.com/
HPLC Applications Database: http://hplcapplications.tosohbioscience.com/

#### TOSOH BIOSCIENCE LLC

3604 Horizon Drive Suite 100, King of Prussia, PA 19406, USA Phone: +1 800 366 4875 Fax: +1 610 272 3028 E-mail: info.tbl@tosoh.com Web site: http://www.tosohbioscience.com/

# TOSOH BIOSCIENCE SHANGHAI CO., LTD.

Room 301, Plaza B, No.1289 Yi Shan Road, Xu Hui District, Shanghai 200233, China Phone: +86 21 3461 0856 Fax: +86 21 3461 0858 E-mail: info@tosoh.com.cn

Web site: http://www.separations.asia.tosohbioscience.com/

# **TOSOH BIOSCIENCE GmbH**

Im Leuschnerpark 4, 64347 Griesheim, Germany Phone: +49 6155 7043700 Fax: +49 6155 8357900 E-mail: info.tbg@tosoh.com Web site: http://www.tosohbioscience.com/

## **TOSOH ASIA PTE. LTD.**

63 Market Street #10-03 Singapore 048942
Phone: +65 6226 5106 Fax: +65 6226 5215
E-mail: info.tsas@tosoh.com
Web site: http://www.separations.asia.tosohbioscience.com/

TSKgel, TSKgel SuperMultipore, TSKgel STAT, BioAssist, Lipopropak, TOYOPEARL, ToyoScreen, TOYOPEARL GigaCap, TOYOPEARL MegaCap, TOYOPAK and EcoSEC are registered trademarks of Tosoh Corporation in Japan, United States, European Union, etc.

HLC is the registered trademark of Tosoh Corporation in Japan and China.

This manual may not be reprinted or copied in whole or in part without written consent of Tosoh Corporation. The contents of the manual are subject to change without notice.

Printed in Japan